

324

Independent Resurvey of the Subdivision of T. 17 S., R. 63 E.

Chains	
	Asc. steep rocky E. slope 200 ft.
5.20	Crest of hill, bears irregularly N. and S.; desc. steep W. slope 135 ft.
11.00	Draw, drains NW.; asc. steep NE. slope 80 ft.
16.60	Spur, projects NW.; desc. steep W. slope 200 ft.
24.00	Base of hill, bears irregularly N. and S., thence across rolling land.
39.93	Point for the $\frac{1}{4}$ sec. cor. of secs. 9 and 16.
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T17S R63E $\frac{1}{4}$ $\frac{S}{S16}$ 1958</p>
	Raise a mound of stone, $3\frac{1}{2}$ ft. base, 24 ins. high, N. of cor.
66.80	H frame power line, bears N. $10^{\circ} 09'$ E. and S. $10^{\circ} 09'$ W.
67.50	Unimproved road, bears N. $10^{\circ} 09'$ E. and S. $10^{\circ} 09'$ W.
79.86	The cor. of secs. 8, 9, 16 and 17.
	Land, broken to rolling desert.
	Soil, rocky to shallow, gravelly.
	Timber, none.
	Undergrowth, creosote brush and scattered sagebrush.
	N. $0^{\circ} 03'$ W., bet. secs. 8 and 9.
	Over rolling desert land.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 8 and 9.
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 16 ins. in the ground, in a mound of stone, $3\frac{1}{2}$ ft. base to top, with brass cap mkd.
	<p style="text-align: center;">T17S R63E $\frac{1}{4}$ $\frac{S}{S8 S9}$ 1958</p>
68.91	Intersect the Fourth Standard Parallel South. Point for the closing cor. of secs. 8 and 9.
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground to solid rock, in a collar of stone, $3\frac{1}{2}$ ft. base to top, with brass cap mkd.
	<p style="text-align: center;">T16S R63E S32 <hr/> S8 S9 C C T17S R63E 1958</p>
	From this closing cor. the standard cor. of secs. 31 and 32, T. 16 S., R. 63 E., bears W. 15.83 chs. dist., an iron post, 2 ins. diam., set mkd. and witnessed as described in the official record.