

Independent Resurvey of the Subdivision of T. 17 S., R. 63 E.

Chains

From the same cor. the standard $\frac{1}{4}$ sec. cor. of sec. 32, T. 16 S., R. 63 E. bears E. 24.17 chs. dist., an iron post, 1 in. diam., set, mkd. and witnessed as described in the official record.

Land, rolling desert.

Soily, shallow, gravelly.

Timber, none.

Undergrowth, scattered creosote bush.

At midpoint bet. the closing cor. of secs. 9 and 10 and the closing cor. of secs. 8 and 9, T. 17 S., R. 63 E.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

$\frac{1}{4}$ S9
T17S R63E
1958

Raise a mound of stone, $3\frac{1}{2}$ ft. base, 24 ins. high, S. of cor.

From this cor. the standard $\frac{1}{4}$ sec. cor. on the S. bdy. of sec. 32, T. 16 S., R. 63 E., bears W. 15.78 chs. dist., an iron post, 1 in. diam., set, mkd. and witnessed as described in the official record.

The $\frac{1}{4}$ sec. cor. on the N. bdy. of sec. 5, T. 18 S., R. 63 E., an iron post, 1 in. diam., set, mkd. and witnessed as described in the official record was remarked in accordance with the special instructions.

T17S R63E
 $\frac{1}{4}$ S32
S 5
T18S
1958

The $\frac{1}{4}$ sec. cor. on the N. bdy. of sec. 6, T. 18 S., R. 63 E., an iron post, 1 in. diam., set, mkd. and witnessed as described in the official record was remarked in accordance with the special instructions.

T17S R63E
 $\frac{1}{4}$ S31
S 6
T18S
1958

From the closing cor. of secs. 5 and 6, T. 18 S., R. 63 E., an iron post, 3 ins. diam., set, mkd. and witnessed as described in the official record and remarked in accordance with special instructions.

T17S R63E
S31 | S32
S6 | S5
T18S
1958

E. $0^{\circ} 03'$ W., over rolling desert land; asc. 69 ft. along SE. slope.