

332

Independent Resurvey of the Subdivision of T. 17 S., R. 63 E.

Chains	
	Raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.
42.50	Wash, 2 ft. deep, 30 lks. wide, drains N. 85° W.; asc. 70 ft..
69.47	The cor. of secs. 7 and 18 on the W. bdy. of T. 17 S., R. 63 E.
	Land, rolling desert.
	Soil, shallow, gravelly.
	Timber, none.
	Undergrowth, creosote bush.
	From the cor. of secs. 7, 8, 17 and 18.
	N. 0° 03' W., bet. secs. 7 and 8.
	Across nearly level land.
4.70	Wash, 2 ft. deep, 30 lks. wide, drains N. 80° E.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 7 and 8.
	Set an iron post, 30 ins. long, 2½ ins. diam., 12 ins. in the ground, in a mound of stone, 3½ ft. base to top, with brass cap mkd.
	T17S R63E
	$\frac{1}{4}$ sec. cor.
	S7 S8
	1958
	Desc. along a slight gentle NE. slope 30 ft.
66.80	Wash, 2 ft. deep, 30 lks. wide, drains N. 75° E.
69.06	Intersect the Fourth Standard Parallel South and point for the closing cor. of secs. 7 and 8.
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T16S R63E
	S31
	S7 S8
	C C
	T17S R63E
	1958
	From this closing cor. the standard Tp. cor. of secs. 31 and 36, T. 16 S., Rs. 62 and 63 E. bears W. 15.86 chs. dist., an iron post, 3 ins. diam., set, mkd. and witnessed as described in the official record.
	From the same cor. the standard $\frac{1}{4}$ sec. cor. of sec. 31, T. 16 S., R. 63 E., bears E. 24.14 chs. dist., an iron post, 1 in. diam., set, mkd. and witnessed as described in the official record.
	Land, rolling desert.
	Soil, shallow, gravelly.
	Timber, none.
	Undergrowth, creosote bush.
	At midpoint bet. the closing cor. of secs. 8 and 9 and the closing cor. of secs. 7 and 8, T. 17 S., R. 63 E., set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.