## Independent Resurvey of the Subdivision of T. 17 S., R. 63 E.

Chains

₹ S8 T17S R63E 1958

Raise a mound of stone, 3½ ft. base, 2 ft. high, S. of cor.

From this cor. the standard & sec. cor. on the S. bdy. of sec. 31, T. 16 S., R. 63 E. bears W. 15.84 chs. dist., an iron post, 1 in. diam., set, mkd. and witnessed as described in the official record.

At a point 40.00 chs. W. of the closing cor. of secs. 7 and 8.

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground with brass cap mkd.

表 S7 T17S R63E 1958

Raise a mound of stone, 2½ ft. base, 2 ft. high, S. of cor.

From this cor. the standard ½ sec. cor. on the S. bdy. of sec. 36, T. 16 S., R. 62 E. bears W. 15.86 chs. dist., an iron post, 1 in. diam., set, mkd. and witnessed as described in the official record.

## General Description

T. 17 S., R. 63 E. consists of rolling and mountainous desert land covered with scattered cactus, bunch grass, black brush and creosote bush. The soil is shallow gravel on the slopes with rocks and ledges in the mountainous portion.

A power line and road enter the township on the south boundary of section 32 and leave the township on the north boundary of section 9. Another road enters the township on the east boundary of section 25, bears southwest and intersects the power line and road in section 32. With the exception of the roads the township can be traveled by four-wheel drive vehicles only.

A branch of the Arrow Canyon Range of mountains extends south through the middle of the township. The drainage is generally east to Dry Lake Valley which borders the east boundary of the township.

The elevation varies from about 2,000 feet above sea level at Dry Lake to 3,050 ft. above sea level on the peaks of the Arrow Canyon Range.

No water was noted during the progress of the survey.