## Dependent Resurvey, E. Bdy., T. 38 N., R. 32 E.

	Dependent Resultey, E. Ddy., 1. 30 N., R. 32 E.
Gl:	
Chains	N. 1° 15' E., bet. secs. 1 and 6.
	Over level land, through greasewood and shadscale.
40.89	The ½ sec. cor. of secs. 1 and 6 at proportionate dist.; there is no remaining evidence of the original cor.
- 3 Ω.	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T38N R32E R33E
	Z Z
	s 1 s 6 1959
81.78	The cor. of Tps. 38 and 39 N., Rs. 32 and 33 E., as determined by old original wood stake, with charred base and 6 faint grooves
	on two sides. lying on mound of dirt.
	At the cor. point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T39N
	R32E R33E
	S36   S31
	S 1 S 6
	T38N
	1959
. 157	
	Land, level. Soil, loam.
	Soil, loam. Vegetation, greasewood and shadscale.
1	
	Dependent Resurvey of North Boundary of T. 38 N., R. 32 E.
* 147 4	Reestablishment of the survey executed by G. W. Garside in 1874.
	From the cor. of Tps. 38 and 39 N., Rs. 32 and 33 E.
	S. 89° 20' W., bet. secs. 1 and 36.
40.65	Over nearly level land, through shadscale and greasewood. The ½ sec. cor. of sec. 1 and 36, mkd. by an old fence cor., accepted by land marks as the original cor. Old fence bears N. and W. at this point.
	At the cor. point
i Line	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
10.14	T39N
	R32E
	\$\frac{\sigma \frac{\sigma \frac{336}{\sigma \frac{1}{3}}}{\sigma \frac{1}{3}}
	T38N 1959
47 - 7	1737
1 1	
	grande in the control of the design of the control