

Dependent Resurvey, N. Bdy., T. 38 N., R. 32 E.

Chains	<p>Set an iron post, 30 ins. long, 2½ ins. in diam., 14 ins. in the ground, and in a mound of stone to top, with brass cap mkd.</p> <p>T39N R32E ½ S31 S 6 T38N 1959</p>
44.80	Dry wash, 40 lks. wide, 1 ft. deep, drains S. 10° W.
63.80	Dry wash, 20 lks. wide, 1 ft. deep, drains S. 20° W.
72.60	Dry wash, 30 lks. wide, 1 ft. deep, drains S.
80.79	<p>The cor. of Tps. 38 and 39 N., Rs. 31 and 32 E.</p> <p>Land, rolling S. slope. Soil, gravel and loam. Vegetation, sagebrush and shadscale.</p>
<p>Dependent Resurvey of the Subdivisional Lines of T. 38 N., R. 32 E.</p>	
<p>Reestablishment of the survey executed by G. W. Garside in 1874. From the cor. of secs. 1, 2, 35 and 36 on the S. bdy. of the Tp. N. 0° 53' E., bet. secs. 35 and 36.</p> <p>Over nearly level land, through greasewood and shadscale.</p>	
35.35	Old dirt road, bears N. 55° E. and S. 55° W.
39.90	<p>The ¼ sec. cor. of secs. 35 and 36 at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p>T38N R32E ½ S35 S36 1959</p>
50.80	Dirt road, bears N. 60° W. and S. 60° E.
56.75	Base of hill; thence asc. 150 ft. over SW. slope.
70.21	Dry wash, 50 lks. wide, 7 ft. deep, drains SW.
79.80	<p>The sec. cor. of secs. 25, 26, 35 and 36, mkd. by stone 20x10x10 ins., firmly set in mound of stone, with 1 groove on S. and E. sides.</p> <p>At the cor. point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a mound of stone to top, with brass cap mkd.</p> <p>T38N R32E S26 S25 S35 S36 1959</p>