

Dependent Resurvey of the South Boundary, T. 26 N., R. 42 E.

Chains

- West, along S. bdy. of sec. 31.
Over gradual S. slope, through scattered sagebrush and shadscale.
- 36.57 Point for the standard $\frac{1}{4}$ sec. cor. of sec. 31.
Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
- SC
T26N R42E
 $\frac{1}{4}$ S31
1959
- 40.42 The original standard $\frac{1}{4}$ sec. cor. of sec. 31, mkd. by a stone, 14x10x8 ins., firmly set, with $\frac{1}{4}$ grooved on the N. face.
At the cor. point
Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
- AP
T26N R42E
S31
1959
- Bury old cornerstone alongside iron post.
- _____
- N. $89^{\circ} 42'$ W., beginning new measurement.
- 12.15 Old road, bears, N. 60° E. and S. 60° W.
- 36.15 Point for the standard $1/16$ sec. cor. of sec. 31.
Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
- SC
T26N R42E
 $1/16$ S31
1959
- 40.45 The original standard sec. cor., remonumented as an AP in 1948, set, mkd. and witnessed as described in the official record.
- _____
- Thence West, beginning new measurement.
- 3.39 The standard cor. of secs. 31 and 36, T. 26 N., Rs. 41 and 42 E., mkd. by an iron post, firmly set, mkd. and witnessed as described in the official record.
Land, gradual S. slope.
Soil, loam.
Timber, none.
Undergrowth, scattered sagebrush and shadscale.

Dependent Resurvey of the West Boundary, T. 26 N., R. 43 E.

Reestablishment of the survey executed by D. H. Barker and J. H. Eaton, Deputy Surveyors, in 1876.