

Dependent Resurvey of the West Boundary of T. 26 N., R. 43 E.

Chains	
	<p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T26N R43E S6 S7 1959</p> <p>Bury old rock cornerstone alongside iron post.</p> <p>Land, nearly level. Soil, loam. Timber, none. Undergrowth, scattered sagebrush and shadscale.</p>
	<p>N. 0° 04' W., along W. bdy. of sec. 6.</p> <p>Over nearly level land.</p>
51.76	Old dirt road, bears E. and W.
26.71	Improved dirt road, bears N. 8° E. and S. 8° W.
34.96	Dry wash, 10 lks. wide, 2 ft. deep, drains E.
35.46	Dry wash, 20 lks. wide, 2 ft. deep, drains S. 50° E.
37.26	Point for the ¼ sec. cor. of sec. 1, T. 26 N., R. 42 E.
	<p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T26N R42E ¼ S1 1959</p>
40.49	<p>The original ¼ sec. cor. of secs. 1 and 6, mkd. by a stone, 8x6x2 ins., firmly set, with ¼ grooved on the W. face. This point now functions as the ¼ sec. cor. of sec. 6 only.</p> <p>At the cor. point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T26N R43E ¼ S6 1959</p> <p>Bury old cornerstone alongside iron post.</p>
	<p>N. 0° 55' W., beginning new measurements.</p>
31.47	Old dirt road, bears N. 29° E. and S. 29° W.
37.71	<p>The original Tp. cor. of Tps. 26 and 27 N., Rs. 42 and 43 E., mkd. by a stone, 14x12x6 ins., firmly set, with 6 grooves on each of the four faces.</p> <p>At the cor. point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mdk.</p>