

Survey, Portion of S. Bdy., T. 28 N., R. 43 E.

Chains	
57.21	Large dry wash, main drainage, 50 lks. wide, 6 ft. deep, drains S. 70° E.
80.00	Point for the cor. of secs. 31 and 32. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T28N R43E S31 S32 1959 Land, rolling hills. Soil, loam, gravel and rocks. Vegetation, shadscale and sagebrush.
	West, along S. bdy. of sec. 31. Asc. steep E. hill.
32.96	Dry wash, drains NE.
40.00	Point for the ¼ sec. cor. of sec. 31. Set an iron post, 28 ins. long, 2½ ins. diam., 12 ins. in the ground, and in a mound of stone to top, with brass cap mkd. T28N R43E ¼ S31 1959 Cont. over steep E. Slope.
79.12	Point for the SE. cor. of T. 28 N., R. 43 E., located due south of the cor. of Tps. 28 and 29 N., R43 E. Set an iron post, 28 ins. long, 2½ ins. diam., 15 ins. in the ground, and in a mound of stone to top, with brass cap mkd. T28N R43E S31 1959 Land, steep E. Slope. Soil, loam, gravel and rocks. Vegetation, sagebrush and shadscale.
Survey of West Boundary of T. 28 N., R. 43 E.	
	North, along W. bdy. of sec. 31. Asc. S. slope, through sagebrush and shadscale.
10.77	Top of large hill; thence desc. steep N. slope.
40.00	Point for the ¼ sec. cor. of sec. 31. Set an iron post, 28 ins. long, 2½ ins. diam., 6 ins. in the ground, and in a mound of stone, to top, with brass cap mkd.