

Survey, W. Bdy., T. 28 N., R. 43 E.

Chains	<div>T28N R43E 1/4 S 7 1959</div>
75.37	Secondary access road, bears E. and W.
80.00	Point for the cor. of secs. 6 and 7. Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div>T28N R42E R43E S 6 S 7 1959</div> Land, low, rolling hills. Soil, loam and gravel. Vegetation, sagebrush and shadscale.
	North, along the W. bdy. of sec. 6. Over nearly level land, through sagebrush and shadscale.
17.40	Primary access road, bears N. 80° E.
19.40	Dry wash, 25 lks. wide, 4 ft. deep, drains N. 80° E.
22.10	Dry wash, 50 lks. wide, 3 ft. deep, drains N. 75° E.
31.05	Dry wash, 20 lks. wide, 2 ft. deep, drains N. 30° E.
40.00	Point for the 1/4 sec. cor. of sec. 6. Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div>T28N R43E 1/4 S 6 1959</div>
79.00	Secondary access road, bears N. 10° E.
80.15	The cor. of Tps. 28 and 29 N., R. 43 E., described in the field notes of the resurvey, T. 29N., R. 43E., 1959. Land, nearly level. Soil, loam and gravel. Vegetation, sagebrush and shadscale.
	Independent Resurvey, Portion of the East Boundary, T 28 N., R 43 E.
	Superseding the survey executed by deputy surveyors Hatch, Eaton and Smyles in 1872. Point for the cor. of T. 28 N., Rs. 43 and 44 E., located on the N. Bdy. of sec. 6, T. 27 N., R. 44 E., at a point South of the SW cor. of sec. 7, T. 28 N., R 44 E. Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.