

6 Dependent Resurvey of the East Boundary of T. 24 N., R. 40 E.

Chains

N. 0° 30' E., bet. secs. 7 and 12.

Over nearly level land, draining NE.

40.15

Point for the $\frac{1}{4}$ sec. cor. of secs. 7 and 12, at proportionate dist.; there is no remaining evidence of the original cor.Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T24N
R40E R41E
 $\frac{1}{4}$
S12 | S 7
1960

No available accessories.

74.50

Trail road, bears W. and N. 70° E.

75.10

Trail road, bears S. 80° E. and N. 80° W.

80.31

The cor. of secs. 1, 6, 7 and 12, monumented by a limestone, 10x6x4 ins., firmly set and properly mkd.

At the cor. point

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

T24N
R40E R41E
 $\frac{1}{4}$
S1 | S6
S12 | S 7
1960

Bury the original cornerstone alongside the iron post.

Land, nearly level.

Soil, light sandy clay.

Timber, none.

Undergrowth, shadscale.

40.06

N. 0° 29' E., bet. secs. 1 and 6.

Over nearly level land, draining NE.

The $\frac{1}{4}$ sec. cor. of secs. 1 and 6, monumented by a limestone, 10x6x4 ins., firmly set and properly mkd.

At the cor. point

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

T24N
R40E R41E
 $\frac{1}{4}$
S1 | S6
1960

Bury the original cornerstone alongside the iron post.

N. 0° 28' E., beginning new measurement.