

Dependent Resurvey, Portion of Subdivisional Lines, T. 25 N., R. 40 E.

Chains	
	From the cor. of secs. 1, 2, 11 and 12.
	N. 89° 53' W., bet. secs. 2 and 11.
	Over gently rolling land.
.30	Small wash, drains SE.
8.20	Trail road, bears S. 85° E. and N. 60° W.
17.90	Wash, 20 lks. wide, 4 ft. deep, drains S. 10° E.
32.00	Wash, 10 lks. wide, 3 ft. deep, drains S. 35° E.
40.10	Point for the $\frac{1}{4}$ sec. cor. of secs. 2 and 11, at proportionate dist.; there is no remaining evidence of the original cor.
	At the cor. point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.
	<p style="text-align: center;">T25N R40E $\frac{1}{4}$ $\frac{S}{S11}$ 1960</p>
50.80	Small wash, drains S. 65° E.
73.30	Trail road, bears S. 20° E. and N. 20° W.
80.20	The cor. of secs. 2, 3, 10 and 11.
	Land, gently rolling. Soil, gravelly sandy clay. Timber, none. Undergrowth, white sage and shadscale.
	N. 3° 18' E., bet. secs. 2 and 3.
	Over rolling land draining SE.
1.80	Small wash, drains E.
16.80	Trail road, bears S. 60° E. and N. 60° W.; thence along rolling W. slope.
39.27	Point for the $\frac{1}{4}$ sec. cor. of secs. 2 and 3, at proportionate dist.; there is no remaining evidence of the original cor.
	At the cor. point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T25N R40E $\frac{1}{4}$ $\frac{S3}{S2}$ 1960</p>
	No available accessories.
	Intersect the Fifth Standard Parallel North.
63.81	Point for the closing cor. of secs. 2 and 3, at proportionate dist.; there is no remaining evidence of the original cor.