Dependent Resurvey, Portion of Subdivisional Lines, T. 25 N., R. 40 E.

1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	Dependent Resurvey, Portion of Subdivisional Lines, T. 25 N., R. 40 E.
Chains	
80.01	Point for the cor. of secs. 3, 4, 9 and 10, at record dist. from the E. and N. bdys.; there is no remaining evidence of the original cor.
	At the cor. point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.
	T25N R40E S4 S3 S 9 S10
	Land, rolling. Soil, gravelly sandy clay. Timber, none.
	Undergrowth, white sage and shadscale.
N N	N. 2° 53' E., bet. secs. 3 and 4.
And a	Over rolling land; desc. 30 ft. over NE slope.
6.00	Wash, 10 1ks. wide, 2 ft. deep, drains NW.; thence along W. slope.
32.50	Same wash, drains NE.
40.05	Point for the ½ sec. cor. of secs. 3 and 4, at proportionate dist.; there is no remaining evidence of the original cor.
	At the cor. point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T25N R40E
	\$4\\$3 1960
	No available accessories.
43.90	Small wash, drains N. 70° E.
***	Intersect the Fifth Standard Parallel North.
65.33	Point for the closing cor. of secs. 3 and 4, at record dist. W. from the original standard cor. of secs. 34 and 35, T. 26 N., R. 40 E., now functioning as an AP; there is no remaining evidence of the original cor.
	At the cor. point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T26N R40E S34 S4 S3 T25N
	CC 1960
	No available accessories.