

Chains

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T25N
R42E R43E
 $\frac{1}{4}$
S12 | S 7
1959

Bury old cor. stone alongside iron post.

N. $0^{\circ} 39'$ E., beginning new measurement.

10.30 Old stage coach road, bears N. 15° E. and S. 15° W.

40.27 The cor. of secs. 1, 6, 7 and 12, mkd. by a stone, $14 \times 12 \times 4$ ins., firmly set, with one groove on N. face and 5 grooves on S. face.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T25N
R42E R43E
S 1 | S 6
S12 | S 7
1959

Bury old cor. stone alongside iron post.

Land, nearly level.

Soil, loam and gravel.

Vegetation, sagebrush and shadscale.

N. $0^{\circ} 36'$ E., bet. secs. 1 and 6.

Over level land, through sagebrush and shadscale.

40.37 The $\frac{1}{4}$ sec. cor. of secs. 1 and 6, mkd. by a stone, $10 \times 8 \times 4$ ins., firmly set, with $\frac{1}{4}$ grooved on the W. face.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T25N
R42E R43E
 $\frac{1}{4}$
S 1 | S 6
1959

Bury old cor. stone alongside iron post.

N. $0^{\circ} 36'$ E., beginning new measurement.

25.66 Intersect Fifth Standard Parallel North. The closing cor. of Tps. 25 N., Rs. 42 and 43 E., mkd. by a stone, $16 \times 12 \times 4$ ins., firmly set, with 6 grooves on all 4 sides.

At the cor. point