

## Dependent Resurvey, W. Bdy., T. 25 N., R. 42 E.

81.54 The cor. of secs. 7, 12, 13 and 18, mkd. by a stone, 12x10x6 ins. firmly set, with 2 grooves on N. face and 4 grooves on S. face. Note: cor. point falls on center line of proposed road.

At the cor. point

Bury old cor. stone, with large cross (X) grooved on it, 18 ins. under the surface.

from which,

An iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., buried 24 ins. in the ground, for reference monument, bears N.  $45^\circ$  W., 40 ft. dist., with brass cap mkd. S12, T25N R41E RM, and an arrow pointing 40 ft. to the true cor.

An iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., buried 24 ins. in the ground, for reference monument, bears S.  $45^\circ$  W., 40 ft. dist., with brass cap mkd. S13, T25N R41E RM and an arrow pointing 40 ft. to the true cor.

Land, nearly level.

Soil, loam.

Vegetation, sagebrush and shadscale.

N.  $0^\circ 26'$  E., bet. secs. 7 and 12.

Over nearly level land.

5.90 Secondary road, bears N.  $60^\circ$  W. and S.  $60^\circ$  E.

40.90 Point for the  $\frac{1}{4}$  sec. cor. of secs. 7 and 12, at proportionate dist.; there is no remaining evidence of the original cor.

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.

T25N  
R41E R42E  
 $\frac{1}{4}$   
S12 | S 7  
1959

81.80 The cor. of secs. 1, 6, 7 and 12, mkd. by a stone, 8x10x7 ins., firmly set, with one groove on N. face and 5 grooves on S. face.

At the cor. point

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.

T25N  
R41E R42E  
S 1 | S 6  
S12 | S 7  
1959

Bury old cor. stone alongside iron post.

Land, nearly level.

Soil, loam.

Vegetation, sagebrush and shadscale.

N.  $1^\circ 01'$  E., bet. secs. 1 and 6.

Over nearly level land.