

Dependent Resurvey, Subdivision, T. 25 N., R. 42 E.

Chains

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T25N R42E

S 2

¼ S11

1959

80.74 The cor. of secs. 2, 3, 10 and 11.

Land, nearly level.

Soil, loam.

Vegetation, sagebrush and shadscale.

N. 0° 58' E., bet. secs. 2 and 3.

Over nearly level land, through sagebrush and shadscale.

40.47 The ¼ sec. cor. of secs. 2 and 3, mkd. by an unmarked stone, 10x8x5 ins., firmly set, and is accepted as the best available evidence of the position for the original cor.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T25N R42E

¼

S 3 | S 2

1959

Bury the original cor. alongside iron post.

Thence

N. 3° 28' E., beginning new measurement.

20.20 Intersect the Fifth Standard Parallel North, point for closing cor. of secs. 2 and 3, at proportionate dist., in an E. and W. direction

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T26N R42E

S35

S 3 | S 2

C C

T25N R42E

1959

From this point, the orig. standard ¼ sec. cor. of sec. 35, T. 26 N., R. 42 E., which is now an angle point, bears S. 89° 44' E., 4.51 chs. dist.

Land, nearly level.

Soil, loam.

Vegetation, sagebrush and shadscale.

The point for the ¼ sec. cor. of sec. 2, is at midpoint and on the N. bdy. of the Tp.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.