

Dependent Resurvey, T. 10 N., R. 43 E.

Chains

The direction of the lines of this survey were determined by altitude observations on the sun for azimuth. The lines were carried forward by sustained angulation, being supplemented by other altitude observations on the sun for azimuth, taken throughout the progress of the survey.

The geographic position for the southeast corner of the township is latitude $38^{\circ}40'29.35''N.$, and longitude $117^{\circ}05'29.49''W.$, as determined from the data furnished with the special instructions. The magnetic declination was read at a number of stations and the average of these readings gave a uniform value of $16^{\circ}30'E.$

Dependent Resurvey of Second Standard Parallel North along the South Boundary of T. 11 N., R. 43 E. Reestablishment of the Survey Executed by C. C. Tracy, Deputy Surveyor, in 1867.

Beginning at the standard cor. of Tps. 11 N., Rs. 43 and 44 E., which is monumented with an iron post, 3 ins. diam., firmly set, marked and witnessed as described in the official record.

N. $89^{\circ} 57' W.$, along the S. bdy. of sec. 36, T. 11 N., R. 43 E.

Over nearly level land, through medium heavy undergrowth.

2.92 The closing cor. of Tps. 10 N., Rs. 43 and 44 E., which is monumented with an iron post, 3 ins. diam., firmly set, marked and witnessed as described in the official record.

40.355 Point for the standard $\frac{1}{4}$ sec. cor. of sec. 36, at proportionate distance; a portion of the original corner post, badly decayed was found lying loose on the ground.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T11N R43E

S C

$\frac{1}{4}$ S 36

T10N R43E

1961

Raise a mound of stone, 4 ft. base, $2\frac{1}{2}$ ft. high, N. of cor.

Continue over gently rolling land, through heavy undergrowth.

60.00 Begin descent; desc. 30 ft. over gradual WSW. slope.

80.00 Graded road, bears N. and S.

80.71 Point for the standard cor. of secs. 35 and 36, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T11N R43E

S C

S 35 | S 36

S 1

T10N R43E

1961