

Dependent Resurvey of Second Standard Parallel
North along the South Boundary of T. 11 N., R. 43 E.

Chains	
40.355	<p>Point for the standard $\frac{1}{4}$ sec. cor. of sec. 32, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T11N R43E S C $\frac{1}{4}$ S 32 T10N R43E 1961</p> <p>Raise a mound of stone, $3\frac{1}{2}$ ft. base, $2\frac{1}{2}$ ft. high, N. of corner.</p> <p>Continue through heavy undergrowth; ascend gradually over NNE. slope.</p>
75.40	<p>Dim road, bears N. and S.</p>
80.71	<p>Point for the standard cor. of secs. 31 and 32, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T11N R43E S C S 31 S 32 T10N R43E S 5 1961</p> <p>Raise a mound of stone, $3\frac{1}{2}$ ft. base, $2\frac{1}{2}$ ft. high, N. of corner.</p> <p>Land, nearly level. Soil, sandy and gravelly clay loam. Timber, none. Undergrowth, sagebrush and rabbit brush.</p>
	<p>N. $89^{\circ} 57'W.$, along the S. bdy. of secs. 31, T. 11 N., R. 43 E.</p> <p>Over slightly rolling land, through heavy undergrowth; asc. 35 ft. over gradual ENE. slope.</p>
2.62	<p>Point for the closing cor. of secs. 5 and 6, T. 10 N., R. 43 E., at proportionate distance; there is no remaining evidence of the original corner.</p>
27.70	<p>Wash, 15 lks. wide, 3 ft. deep, drains ESE.</p>
33.40	<p>Road, bull-dozed, bears NE. and SW.</p>
40.355	<p>Point for the standard $\frac{1}{4}$ sec. cor. of sec. 31, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T11N R43E S C $\frac{1}{4}$ S 31 T10N R43E 1961</p>