

## Dependent Resurvey of the South Boundary, T. 10 N., R. 43 E.

## Chains

firmly set, marked and witnessed as described in the official record.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground with brass cap mkd.

T10N R43E

¼ S 32  
S 5

T9N R43E

1961

Raise a mound of stone, 3 ft. base, 2 ft. high, N. of corner.

Set the original corner post along side the iron post.

N. 89° 09' W., beginning new measurement.

21.60 Trail road, bears NE. and SW.

22.20 Trail road, bears N. 65° E. and S. 65° W.

22.40 Graded road, bears NE. and SW.

39.82 The cor. of secs. 5, 6, 31 and 32, monumented with a squared post firmly set, marked and witnessed as described in the official record.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T10N R43E

S 31 | S 32  
S 6 | S 5

T9N R43E

1961

Raise a mound of stone, 3 ft. base, 2 ft. high, N. of corner.

Set the original corner post along side the iron post.

Land, nearly level.

Soil, sandy clay.

Timber, none.

Undergrowth, sagebrush and creosote bush.

N. 89° 26' W., bet. secs. 6 and 31.

Over nearly level land through medium dense undergrowth.

40.33 The ¼ sec. cor. of secs. 6 and 31, monumented with a square post, firmly set, marked and witnessed as described in the official record.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T10N R43E

¼ S 31

S 6

T9N R43E

1961