

Dependent Resurvey of the Reese River Guide Meridian
through T. 10 N., between Rs. 42 and 43 E.

Chains	Continue descent; desc. 20 ft. over N. slope.
41.60	Wash, 30 lks. wide, 4 ft. deep, drains E., asc. 20 ft. along E. slope.
57.60	Top of ascent, desc. 130 ft. over NNE. slope.
77.10	Ravine, drains E., asc. 30 ft. over S. slope.
79.38	The corner of Ts. 10 and 11 N., Rs. 42 and 43 E.
	Dependent Resurvey of the Subdivisional Lines, T. 10 N., R. 43 E.
	Reestablishment of the Survey Executed by A. J. Hatch, D. H. Barker and E. L. Bridges, Deputy Surveyors, in 1873.
	Beginning the subdivisional survey at the cor. of secs. 1, 2, 35 and 36, on thw S. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., hereinbefore described.
	N. 1° 00' E., bet. secs. 35 and 36.
	Over gently rolling land through medium dense undergrowth.
18.20	Wash, 30 lks. wide, 2 ft. deep, drains W.
27.00	Wash, 20 lks. wide, 2 ft. deep, drains W.
39.95	Point for the ¼ sec. cor. of secs. 35 and 36, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<div>T10N R43E ½ S35 S36 1961</div>
	Deposit broken glass, around the iron post, 6 ins. below the surface of the ground.
	Raise a mound of stone, 3 ft. base, 2 ft. high, W. of corner.
42.10	Wash, 10 lks. wide, 2 ft. deep, drains WNW.
57.60	Wash, 20 lks. wide, 2 ft. deep, drains W.
66.50	Wash, 20 lks. wide, 2 ft. deep, drains W.
69.30	Wash, 30 lks. wide, 3 ft. deep, drains WNW.
79.90	Point for the cor. of secs. 25, 26, 35 and 36, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground with brass cap mkd.