Dependent Resurvey o	the	Subdivisional	Lines,	T.	10	Ν.,	R.	43	Ε.
----------------------	-----	---------------	--------	----	----	-----	----	----	----

	Dependent Resurvey of the Subdivisional Lines, T. 10 N., R. 43 E.
Chains	
	N. 0° 01' W., bet. secs. 1 and 2.
	Over gently rolling land through medium dense undergrowth.
.20	Wash, 1.00 chain wide, 6 ft. deep, drains WNW.
13.70	Wash, 50 lks. wide, 5 ft. deep, drains WNW.
39.94	Point for the ½ sec. cor. of secs. 1 and 2, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
a sa an	T10N R43E
v 5 %	S2   S1 1961
	Raise a mound of stone, 3 ft. base, 2 ft. high, W. of corner.
	Deposit broken glass around the iron post, 6 ins. below the surface of the ground.
42.50	Trail road, bears SE. and NW.
52.30	Wash, 20 1ks. wide, 3 ft. deep, drains W.
57.10	Graded road, bears SE. and NW.
59.70	Wash, 20 1ks. wide, 2 ft. deep, drains WNW.
69.40	Wash, 30 1ks. wide; 3 ft. deep, drains W.
80.84	Intersect the Second Standard Parallel North.
	Point for the closing cor. of secs. 1 and 2, a portion of the original corner post, badly decayed was found lying loose on the ground.
_ x	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T11N R43E
-	$\frac{\text{S}}{\text{S}} \frac{35}{2   \text{S}} 1$
	C C T10N R43E
-1 , 3	1961
W-00-00	Raise a mound of stone, 3½ ft. base, 2½ ft. high, S. of cor.
	From this corner, the standard cor. of secs. 35 and 36, T. 11 N., R. 43 E., monumented with an iron post, 2½ ins. diam., hereinbefore described bears S. 89° 57' E., 2.82 chs. dist.
	From this same corner, the standard ½ sec. cor. of sec. 35, T. 11 N., R. 43 E., monumented with an iron post, 2½ ins. diam., hereinbefore described, bears N. 89° 57' W.
	Land, gently rolling. Soil, sandy clay. Timber, none. Undergrowth, sagebrush.

The point for the N.  $\frac{1}{4}$  sec. cor. of sec. 1 is at midpoint and on the N. bdy. of the Tp.