

Dependent Resurvey of the Subdivisional Lines, T. 10 N., R. 43 E.

Chains

Deposit broken glass, around the iron post, 6 ins. below the surface of the ground.

Continue over nearly level land, through dense undergrowth.

51.30 Diversion ditch, 10 lks. wide, 1 ft. deep, bears NW. and SE. Water flows NW.

65.60 Road, bladed, bears NW. and SE.

79.66 The cor. of secs. 4, 5, 8 and 9.

Land, nearly level.

Soil, sandy and gravelly clay loam.

Timber, none.

Undergrowth, sagebrush and rabbit brush.

N. 1° 24' W., bet. secs. 4 and 5.

Over nearly level land, through heavy undergrowth.

9.20 Road, bladed, bears NW. and SE.

39.74 Point for the $\frac{1}{2}$ sec. cor. of secs. 4 and 5, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T10N R43E

$\frac{1}{2}$
S 5 | S 4

 1961

Deposit broken glass, around the iron post, 6 ins. below the surface of the ground.

Continue over nearly level land, through dense undergrowth.

44.55 Diversion ditch, 10 lks. wide, 3 ft. deep, bears E. and W. Water flows E.

60.45 Diversion ditch, 10 lks. wide, 3 ft. deep, bears E. and W. Water flows E.

61.85 Fence, 3 strands barbed wire on wooden posts, bears E. and W.

80.27 Intersect Second Standard Parallel North.

Point for the closing cor. of secs. 4 and 5; there is no remaining evidence of the original corner.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T11N R43E

 S 32
S 5 | S 4

 C | C

T10N R43E

 1961

Raise a mound of stone, 3½ ft. base, 2½ ft. high, S. of cor.

Deposit broken glass, around the iron post, 6 ins. below the surface of the ground.