

## Dependent Resurvey of the Subdivisional Lines, T. 10 N., R. 43 E.

Chains	
	T10N R43E $\frac{1}{4}$ $\frac{S 8}{S17}$ 1961
	Deposit broken glass, around the iron post, 6 ins. below the surface of the ground.
	Continue over undulating land, through heavy undergrowth.
64.80	Road, bladed, bears NE. and SW.
75.20	Summit creek, dry, 50 lks. wide, 3 ft. deep, course NE.
79.02	The cor. of secs. 7, 8, 17, and 18.
	Land, undulating. Soil, sandy and gravelly clay loam. Timber, none. Undergrowth, sagebrush and rabbit brush.
	West, bet. secs. 7 and 18.
	Over undulating land, through heavy undergrowth.
20.30	Telephone line, single wire, on wooden poles, bears N. 20°00' E., and S. 20°00' W.
32.60	Wash, 20 lks. wide, 3 ft. deep, drains NE.
39.00	Main wash, dry, 80 lks. wide, 4 ft. deep, drains NE.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 7 and 18, at record distance; there is no remaining evidence of the original corner.
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T10N R43E $\frac{1}{4}$ $\frac{S 7}{S18}$ 1961
	Deposit broken glass, around the iron post, 6 ins. below the surface, of the ground.
40.20	Road, bladed, bears NE. and S., begin ascent; asc. 230 ft. over ESE. slope.
69.40	Base of rough high rocky hill in Toiyabe range, bears N. and S. 30° W., ascend 400 ft. over abrupt E. slope.
81.89	Intersect the Reese River Guide Meridian, W. bdy. of the Tp.
	Point for the cor. of secs. 7 and 18.
	Set an iron post, 30 ins. long, 2½ ins. diam., 14 ins. in the ground, to solid rock, and in a mound of stone to top, with brass cap mkd.
	T10N R43E R42E   $\frac{S 7}{S18}$ 1961
	Land, eastern half, undulating; western half, gently rolling to rough, broken mountainous.