5 1	D	o.f	+100	Subdivisional	Tines	T	10	N	R	43	E
Dependent	Resurvey	OĪ	the	Subdivisional	Lines,	T .	TO	14.	V.	45	L.

	10	Dependent Resurvey of the Subdivisional Lines, T. 10 N., R. 43 E.
	Chains	22' E.
		From the cor. of secs. 5, 6, 7 and 8.
_		N. 2° 26' W., bet. secs. 5 and 6.
		Over undulating land, through heavy undergrowth.
3	7.44	Point for the ½ sec. cor. of secs. 5 and 6, at proportionate distance; there is no remaining evidence of the original corner.
		Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
		TION R43E
	*	S 6 S 5 1961
	-	Deposit broken glass, around the iron post, 6 ins. below the surface of the ground.
		Continue over undulating land, through heavy undergrowth.
7	75.45	Intersect the Second Standard Parallel North.
		Point for the closing cor. of secs. 5 and 6.
	-	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
		T11N R43E S 31
	, 8	S 6 S 5 C C T10N R43E 1961
	"	Raise a mound of stone, $3\frac{1}{2}$ ft. base, $2\frac{1}{2}$ ft. high, S. of cor.
	*	From this corner, the standard cor. of secs. 31 and 32, T. 11 N., R. 43 E., monumented with an iron post, 2½ ins. diam., hereinbefore described, bears S. 89° 57' E., 2.62 chs. dist.
		From this same corner, the standard $\frac{1}{4}$ sec. cor. of sec. 31, T. 11 N., R. 43 E., monumented with an iron post, $2\frac{1}{2}$ ins. diam., hereinbefore described, bears N. 89° 57' W.
		Land, undulating. Soil, sandy and gravelly clay loam. Timber, none. Undergrowth, sagebrush and rabbit brush.
	:	The point for the N. $\frac{1}{4}$ sec. cor. of sec. 5 is at midpoint and on the N. bdy. of the Tp.
		At the corner point
	ж. "	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
		T11N R43E
	year V	え S 5 T10N R43E 1961
		Raise a mound of stone, $3\frac{1}{2}$ ft. base, $2\frac{1}{2}$ ft. high, S. of cor.