

## Dependent Resurvey of the First Standard Parallel N. through R. 40 E.

Chains	
36.28	Intersect line bet. cor. 2 and 3, at a point from which the cor. No. 2 bears N. 20° 35' E., 1.21 chs. dist. Cor. No. 2, which is monumented by a wood post (4x4 ins.) mkd. cor. No. 2 - MS 4414, set firmly in a large mound of stone; thence asc. 30 ft. over rocky and broken NE. slope.
38.64	The standard cor. of secs. 31 and 32, monumented by a stone, 14x10x8 ins., mkd. 5 notches on E. and 1 notch on W. faces, firmly set, and the remains of a mound of stone N. of cor.  At the cor. point  Set an iron post, 30 ins. long, 2½ ins. diam., 14 ins. in the ground, in a mound of stone, 6 ft. base to top, with brass cap mkd.  T6N R40E S C <u>S31   S32</u> 1959  Deposit original stone alongside iron post.  Land, rough and broken. Soil, clay and rocky. Timber, none. Undergrowth, none.
	N. 88° 15' W., along the S. bdy. of sec. 31.  Asc. 40 ft. over rocky NE. to E. slope; no undergrowth.
8.50	Rocky Ridge spur, slopes NW.; desc. 70 ft. over rocky W. slope.
15.40	Wash, drains N.; thence over rolling N. slope.
36.30	Wash, drains NE.; thence asc. 20 ft. over S. to SE. slope.
42.34	The standard ¼ sec. cor. of sec. 31, which is monumented by a stone, 20x8x8 ins., unmarked, firmly set in a mound of stone.  At the cor. point  Set an iron post, 30 ins. long, 2½ ins. diam., 15 ins. in the ground, in a mound of stone, 6 ft. base to top, with brass cap mkd.  T6N R40E S C ¼ <u>S31</u> 1959  Deposit original stone alongside iron post.  This cor. falls on steep rocky S. slope.
	N. 87° 15' W., beginning new measurement.  Asc. 30 ft. along and over rolling S. to SE. slope; no undergrowth.
15.10	Saddle, bears N. and S.; thence along rolling S. slope.
32.08	The closing cor. of Tps. 5 N., Rs. 39 and 40 E., secs. 1 and 6, which is monumented by a set stone, 12x8x6 ins., mkd. with 6 notches on the E., S. and W. faces, firmly set, in a mound of stone S. of cor.