

Chains	<p>N. 0° 05' E., beginning new measurement.</p> <p>Over rolling E. to NE. slope.</p>
40.24	<p>The cor. of Tps. 6 and 7 N., Rs. 39 and 40 E., secs. 1, 6, 31 and 36, which is monumented by a stone, 8x8x8 ins., mkd. with 6 notches on E., S., W. and N. faces, firmly set, and with a mound of stone S. of cor.</p> <p>At the cor. point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <div><div>T7N</div><div>R39E R40E</div><div>S36 S31</div><div>S1 S6</div><div>T6N</div><div>1959</div></div> <p>Deposit original stone alongside iron post.</p> <p>Deposit broken glass alongside iron post.</p> <p>Raise a mound of stone S. of cor.</p> <p>Land, rolling, Soil, sandy loam to rocky, Timber, none, Undergrowth, desert vegetation.</p> <hr/> <p>Dependent Resurvey of Subdivisional Lines of T. 6 N., R. 40 E.</p> <hr/> <p>Reestablishment of the survey executed by Glover and Perrin, Deputy Surveyors, in 1880.</p> <hr/> <p>From the standard cor. of secs. 35 and 36, on the S. bdy. of the Tp. N. 0° 26' W., bet. secs. 35 and 36.</p> <p>Over nearly level land, through desert vegetation.</p>
40.31	<p>Point for the ¼ sec. cor. of secs. 35 and 36, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground with brass cap mkd.</p> <div><div>T6N R40E</div><div>¼</div><div>S35 S36</div><div>1959</div></div> <p>Deposit broken glass alongside iron post.</p> <p>Raise a mound of stone, W. of cor.</p>
46.30	<p>Road, bears N. 27° W. and S. 27° E.</p>
80.62	<p>Point for the cor. of secs. 25, 26, 35 and 36, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p>