Dependent Resurvey	of	the	Subdivisional	Lines	of	т.	6	Ν.,	R.	40	Ε.
--------------------	----	-----	---------------	-------	----	----	---	-----	----	----	----

	Dependent Resurvey of the Subdivisional Lines of T. 6 N., R. 40 E.
Chains 40.19	The ½ sec. cor. of secs. 4 and 5, which is monumented by a stone, 12x10x8 ins., mkd. ½ on W. face, firmly set in a mound of stone.
	At the cor. point
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap mkd.
	T6N R40E S5 S4 1959
	Deposit original stone alongside iron post.
	Deposit broken glass alongside iron post.
	Raise a mound of stone W. of cor.
_	
The DAY BOT DO	N. 2° 04' E., beginning new measurement.
	Over nearly level land, through desert vegetation.
15.30	Power line, bears N. 34° 15' W. and S. 34° 15' E.
16.60	Road, parallel to power line.
40.35	The cor. of secs. 4, 5, 32 and 33, on the N. bdy. of the Tp., which is monumented with an iron post, set, mkd. and witnessed as described in the resurvey of T. 7 N., R. 40 E.
s 2	Land, nearly level. Soil, sandy loam. Timber, none. Undergrowth, desert vegetation.
K	From the standard cor. of secs. 31 and 32, on the S. bdy. of the Tp.
-	N. 3° 21' W., bet. secs. 31 and 32.
	Desc. 60 ft. over rocky N. slope, through desert vegetation.
15.80	Wash, 6 ft. deep, 1 ch. wide, drains E.; asc. over rolling S. to SE. slope.
41.62	Point for the ½ sec. cor. of secs. 31 and 32, at proportionate dist. there is no remaining evidence of the original cor.
	Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.
	T6N R40E
	S31 S32 1959
a a	Raise a mound of stone W. of cor.
83.23	The cor. of secs. 29, 30, 31 and 32, which is monumented by a stone, 20x16x10 ins., mkd. 1 notch on S. and 5 notches on E. faces, firmly set in a mound of stone.
v 1000	At the cor. point
_	