

Dependent Resurvey of the West Boundary of T. 7 N., R. 40 E.

	Chains	Reestablishment of the survey executed by Glover and Perrin, Deputy Surveyors, in 1880.
		N. 0° 32' E., bet. secs. 31 and 36.
		Over rolling E. slope, through desert vegetation.
40.56		Point for the $\frac{1}{4}$ sec. cor. of secs. 13 and 32, at proportionate dist.; there is no remaining evidence of the original cor.
		Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.
		<div>T7N R39E R40E $\frac{1}{4}$ S36 S31 1959</div>
		Deposit broken glass alongside iron post.
		Raise a mound of stone W. of cor.
81.12		Point for the cor. of secs. 25, 30, 31 and 36, at proportionate dist.; there is no remaining evidence of the original cor.
		Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.
		<div>T7N R39E R40E S25 S30 S36 S31 1959</div>
		Deposit broken glass alongside iron post.
		Raise a mound of stone W. of cor.
		Land, rolling. Soil, sandy loam and rocky. Timber, none. Undergrowth, desert vegetation.
		N. 0° 32' E., bet. secs. 25 and 30.
		Over rolling E. slope, through desert vegetation.
40.56		Point for the $\frac{1}{4}$ sec. cor. of secs. 25 and 30, at proportionate dist.; there is no remaining evidence of the original cor.
		Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.
		<div>T7N R39E R40E $\frac{1}{4}$ S25 S30 1959</div>
		Deposit broken glass alongside iron post.
		Raise a mound of stone W. of cor.
81.12		The cor. of secs. 19, 24, 25 and 30, which is monumented by a stone, 14x10x8 ins., unmarked, and set in a mound of stone.