

## TOWNSHIP 15 NORTH, RANGE 19 EAST

## CHAINS

T15N R19E

$$\frac{1}{4} \frac{S \ 7}{S \ 18}$$

1966

reset the original corner post alongside the iron post.

from this corner

The new bearing trees:

A fir, 10 ins. diam., bears S. 77° E., 71 lks.  
dist., mkd. T15N R19E  $\frac{1}{4}$  S18 BT.

A fir, 10 ins. diam., bears N. 43° W., 73 lks.  
dist., mkd. T15N R19E  $\frac{1}{4}$  S7 BT.

## TOWNSHIP 18 NORTH, RANGE 18 EAST

These field notes are those of a remonumentation of certain corners of the survey executed by Solomon W. Foreman, Deputy Surveyor, in 1865.

The cor. of secs. 15, 16, 21 and 22, monumented with a granite stone, 14x12x6 ins., firmly set and plainly mkd. with 3 notches on S. face and 3 notches on the E. face and witnessed by original bearing trees.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

$$\begin{array}{cc} T18N & R18E \\ S \ 16 & | \ S \ 15 \\ S \ 21 & | \ S \ 22 \end{array}$$

1966

bury the original corner stone alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

from this corner

The original bearing trees:

A pine, 10 ins. diam., bears N. 50° E., 20 lks.  
dist., mkd. T18N R18E S15 BT.

A pine, 16 ins. diam., bears S. 60° E., 60 lks.  
dist., mkd. T18N R18E S22 BT.

A pine, 16 ins. diam., bears S. 16° W., 65 lks.  
dist., mkd. T18N R18E S21 BT.

A pine, 18 ins. diam., bears N. 35° W., 10 lks.  
dist., mkd. T18N R18E S16 BT.