

TOWNSHIP 18 NORTH, RANGE 18 EAST

CHAINS

T18N	R18E
S 4	
$\frac{1}{4}$	S 9

1966

from which

The original bearing trees:

A pine, 30 ins. diam., bears N. 15° E., 17 lks. dist., mkd. $\frac{1}{4}$ S4 BT. (Record)

A pine, 40 ins. diam., bears S. 30° W., 66 lks. dist., mkd. $\frac{1}{4}$ S9 BT. (Record)

This corner sets on rocky NW. slope.

The $\frac{1}{4}$ sec. cor. of secs. 4 and 33, on the N. bdy. of the Tp., monumented with a limestone, 16x8x6 ins., plainly mkd. $\frac{1}{4}$ on N. face and firmly set in a mound of stone.

At the corner point

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 10 ins. in the ground to bedrock and in a mound of stone to cap, 3 ft. base, with brass cap mkd.

T19N	R18E
S 33	
$\frac{1}{4}$	S 4
	T18N

1966

bury the original corner stone alongside the iron post.

This corner sets on a NW. slope. A bladed road, bearing N. and S., is 3.00 chs. W.

The cor. of secs. 4, 5, 32 and 33, on the N. bdy. of the Tp., monumented with a granite stone, 20x12x10 ins., plainly mkd. with 4 notches on E. face and 2 notches on W. face and firmly set in a mound of stone.

At the corner point

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., over a cross (X) on solid rock and in a mound of stone to cap, 5 ft. base, with brass cap mkd.

T19N	R18E
S 32	S 33
S 5	S 4
	T18N

1966

bury the original corner stone alongside the iron post.

from which

The original bearing trees: