Remonumentation of Corners T. 8 N., R. 42 E., M.D. Mer.

Chains

Place collar of rock around, and raise a mound of stone, 2x12 ft. W. of cor.

Corner is located on gentle SW. slope, approx. 5 chs. dist. E. from the main road leading to ranches and Peavine canyon.

Note: Tellurometer triangulation station BLM U-71-6, 1961, bears approx. S. about 4 chs. dist.

At the cor. of secs. 20, 21, 28 and 29, T. 8 N., R. 42 E., which is mkd. by a cedar stake, 3 ft. long, 2 ins. diam., sq. at the top, marks have weathered off, set in a mound of stone. An old Forest Service iron pipe is set 5 lks. E. of post. This corner was found by R. D. Garver, Forest Service Surveyor, in 1913, who at that time found scribe marks on the post.

At cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, over broken glass, with orig. cor. post set alongside; brass cap mkd.

T8N R42E <u>\$20</u> | <u>\$21</u> <u>\$29</u> | <u>\$28</u> 1961

Place collar of rock around, and raise a mound of stone, 3 ft. \times 2 ft. \times 0 fc.

Remonumentation of Corners, T. 12 N., R. 42 E., M.D. Mer.

The north, south, and west boundaries and a portion of the subdivisional lines were surveyed by Hatch, Barker and Bridges in 1873. The east boundary was surveyed by Tracy in 1867.

The following field notes are those of the remonumentation of certain identified original corners in T. 12 N., R. 42 E., M.D. Mer., Nevada. The position of each corner was marked by the original monument, or determined from corner accessories recorded in the original survey record.

The corners remonumented were selected by the Forest Service as being adjacent to, or controlling the boundaries of Forest Service Lands. The remonumentation was requested by and accomplished in cooperation with the Forest Service.

T. 12 N., R. 42 E.

At the $\frac{1}{4}$ sec. cor. of secs. 23 and 24, T. 12 N., R. 42 E., which is a granite stone, $11\times10\times6$ ins., firmly set in the ground marked $\frac{1}{4}$ on E. face, loosely set in a small mound of stone. An old Forest Service post is set alongside.

At cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, over broken glass, with orig. cor. stone buried on W. side of post; brass cap marked

T12N R42E S23 S24

Raise a mound of stone, around post.