

TOWNSHIP 14 NORTH, RANGE 40 EAST

CHAINS

These field notes are those of a remonumentation of certain corners of the survey executed by A. J. Hatch, D. H. Barker and E. L. Bridges, U. S. Deputy Surveyors, in 1873.

The cor. of Tps. 14 and 15 N., Rs. 40 and 41 E., monumented with a granite stone, 12x10x8 ins., plainly mkd. with 6 notches on the S., E., N. and W. edges and firmly set in a mound of stone.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground and in a collar of stone, with brass cap mkd.

T15N	
R40E	R41E
S 36	S 31
S 1	S 6
T14N	

1967

bury the original corner stone and set a steel fence post, 6 ft. long, 2 ft. in the ground, alongside the iron post.

The cor. of secs. 1, 6, 7 and 12, on the E. bdy. of the Tp., monumented with a stone, 22x10x10 ins., plainly mkd. with 1 groove on the N. face, 5 grooves on the S. face and firmly set in the ground.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T14N	
R40E	R41E
S 1	S 6
S 12	S 7

1967

bury the original corner stone and set a steel fence post, 6 ft. long, 2 ft. in the ground, alongside the iron post.

TOWNSHIP 16 NORTH, RANGE 39 EAST
MOUNT DIABLO MERIDIAN, NEVADA

These field notes are those of a remonumentation of certain corners of the survey executed by Barker and McClellan, U. S. Deputy Surveyors, in 1879.

The standard cor. of T. 16 N., Rs. 39 and 40 E., on the Third Standard Parallel North, monumented with a granite stone, 18x14x10 ins., plainly mkd. with 6 grooves on the E., W. and N. faces and firmly set in the ground with a small mound of stone N. of cor.