

TOWNSHIP 16 NORTH, RANGE 39 EAST

CHAINS

reset the original corner stone and set a steel fence post, 6 ft. long, 2 ft. in the ground, alongside the iron post and raise a mound of stone, 2 ft. base, 2 ft. high, W. of cor.

TOWNSHIP 16 NORTH, RANGE 40 EAST
MOUNT DIABLO MERIDIAN, NEVADA

These field notes are those of a remonumentation of certain corners of the survey executed by Barker and McClellan, U. S. Deputy Surveyors, in 1879.

The 1/4 sec. cor. of secs. 19 and 24, on the E. bdy. of the Tp., monumented with a stone, 16x11x9 ins., plainly mkd. 1/4 on the W. face and firmly set alongside a steel fence post, exposed 5 ft. above ground.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

T16N
R40E R41E
1/4
S 24 | S 19

1967

bury the original corner stone and reset the steel fence post, 7 ft. long, 2 1/2 ft. in the ground, alongside the iron post.

The cor. of secs. 13, 18, 19 and 24, on the E. bdy. of the Tp., monumented with a stone, 14x9x8 ins., plainly mkd. with 3 grooves on the N. face, 3 grooves on the S. face and firmly set in the ground with a small mound of stone W. of cor.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

T16N
R40E R41E
S 13 | S 18
S 24 | S 19

1967

bury the original corner stone and set a steel fence post, 7 ft. long, 2 1/2 ft. in the ground, alongside the iron post.