

TOWNSHIP 16 NORTH, RANGE 40 EAST

CHAINS

bury the original corner stone and set a steel fence post, 7 ft. long, 2½ ft. in the ground, alongside the iron post.

The cor. of Tps. 16 and 17 N., Rs. 40 and 41 E., monumented with a cottonwood post, 2x2x48 ins., dimly scribed and loosely set in a mound of earth.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T17N	
R40E	R41E
<u>S 36</u>	<u>S 31</u>
S 1	S 6
T16N	

1967

reset the cottonwood post and set a steel fence post, 6 ft. long, 2 ft. in the ground, alongside the iron post.

The cor. of secs. 23, 24, 25 and 26, monumented with a stone, 16x11x8 ins., dimly mkd. with 4 grooves on the N. face, 2 grooves on the S. face and firmly set in a mound of stone.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 6 ins. in the ground to bedrock and in a mound of stone to cap, 4 ft. base, with brass cap mkd.

T16N	R40E
<u>S 23</u>	<u>S 24</u>
S 26	S 25

1967

reset the original corner stone and set a steel fence post, 6 ft. long, 1½ ft. in the ground, alongside the iron post.

The ¼ sec. cor. of secs. 23 and 24, monumented with a stone, 20x15x10 ins., plainly mkd. ¼ on the W. face and firmly set in a mound of stone.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground and in a collar of stone, with brass cap mkd.

T16N	R40E
S 23	S 24

1967