

TOWNSHIP 12 NORTH, RANGE 40 EAST

CHAINS

These field notes are those of a remonumentation of certain corners of the survey executed by Hatch, Bridges and Barker, Deputy Surveyors, in 1873.

The cor. of Tps. 12 and 13 N., Rs. 40 and 41 E., monumented with a granite stone, 16x12x6 ins., firmly set and plainly mkd. with 6 notches on the N., S., E. and W. faces.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.

T13N	
R40E	R41E
S 36	S 31
S 1	S 6
T12N	

1965

bury the original cornerstone alongside the iron post and set a steel fence post, 6 ft. long, 24 ins. in the ground alongside.

This corner is on a gradual West slope in medium growth of sagebrush. A trail road bearing WNW. and ESE. is about 1.90 chains south, and Stewart Creek is about 7 chains south of the corner.

The cor. of secs. 4, 5, 32 and 33, monumented with a granite stone, 11x8x7 ins., firmly set with a small mound of stone to N., and plainly mkd. with 4 notches on the E. face and 2 notches on the W. face.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T13N	R40E
S 32	S 33
S 5	S 4
T12N	

1965

bury the original cornerstone alongside the iron post, raise a mound of stone, 2 ft. base, 2 ft. high, W. of cor. and set a steel fence post, 6 ft. long, 24 ins. in the ground alongside.

This corner is on W. side of small draw draining NE. A trail road bearing NW. and SE. is approximately 5 chains south of the corner.

The cor. of secs. 16, 17, 20 and 21, monumented with a granite stone, 10x9x7 ins., firmly set along a fence