

## TOWNSHIP 12 NORTH, RANGE 40 EAST

## CHAINS

bearing E. and W. 0.62 chs., thence N., and plainly mkd. with 3 notches on the S. face and 4 notches on the E. face.

At the corner point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 22 ins. in the ground, with brass cap mkd.

T12N	R40E
S 17	S 16
S 20	S 21

1965

from which

A pinon, 14 ins. diam., bears N.  $36-1/4^\circ$  E., 58 lks. dist., mkd. T12N R40E S16 BT.

A pinon, 18 ins. diam., bears S.  $23-3/4^\circ$  W., 30 lks. dist., mkd. S20 BT.

A pinon, 6 ins. diam., bears S.  $73^\circ$  W., 64 lks. dist., mkd. T12N R40E S20 BT.

No trees available in secs. 17 and 21.

bury the original cornerstone alongside the iron post and set a steel fence post, 6 ft. long, 24 ins. in the ground alongside.

A spur, 50 links east, slopes NNE.

The cor. of secs. 8, 9, 16 and 17, monumented with a granite stone, 12x8x4 ins., firmly set and plainly mkd. with 4 notches on the S. face and 4 notches on the E. face.

At the corner point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 22 ins. in the ground, with brass cap mkd.

T12N	R40E
S 8	S 9
S 17	S 16

1965

bury the original cornerstone alongside the iron post and set a steel fence post, 6 ft. long, 24 ins. in the ground alongside.

This corner is on a gradual E. slope in medium growth of sagebrush. Fence bearing northerly and southerly is approximately 5 chains west. Reese River road is approximately 21 chains east of corner.

## TOWNSHIP 14 NORTH, RANGE 40 EAST

These field notes are those of a remonumentation of