

TOWNSHIP 14 NORTH, RANGE 40 EAST.

CHAINS

alongside.

The cor. of secs. 15, 16, 21 and 22, monumented with a granite stone, 22x12x8 ins., firmly set in cor. of fence bearing N. and W. and plainly mkd. with 3 notches on the S. face and 3 notches on the E. face.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T14N	R40E
S 16	S 15
S 21	S 22

1965

bury the original cornerstone alongside the iron post and set a steel fence post, 6 ft. long, 24 ins. in the ground alongside.

TOWNSHIP 14 NORTH, RANGE 41 EAST

These field notes are those of a remonumentation of certain corners of the survey executed by Hatch, Bridges and Barker, Deputy Surveyors, in 1873, and resurveyed in part by Thurtell and Kearney, Deputy Surveyors, in 1909.

The ¼ sec. cor. of secs. 3 and 34, monumented with a granite stone, 14x14x8 ins., firmly set along bladed trail bearing N. and W. and plainly mkd. ¼ on the N. face.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T14N	R41E
¼ S 34	
¼ S 3	
T13N	

1965

bury the original cornerstone alongside the iron post, set a steel fence post, 6 ft. long, 24 ins. in the ground alongside and raise a mound of stone, 2 ft. base, 2 ft. high, N. of cor.

The cor. of secs. 3, 4, 33 and 34, monumented with a granite stone, 16x12x8 ins., firmly set along bladed trail bearing S. and E. and dimly mkd. with 3 notches on the E. face and 3 notches on the W. face.