

TOWNSHIP 14 NORTH, RANGE 41 EAST

CHAINS

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

T14N	R41E
S 33	S 34
S 4	S 3
T13N	

1965

bury the original cornerstone alongside the iron post, set a steel fence post, 6 ft. long, 24 ins. in the ground alongside and raise a mound of stone, 2 ft. base, 2 ft. high, W. of cor.

The $\frac{1}{4}$ sec. cor. of secs. 11 and 12, monumented with a granite stone, 14x12x6 ins., firmly set and plainly mkd. $\frac{1}{4}$ on the W. face and witnessed by an original bearing tree.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

T14N	R41E
S 11	S 12

1965

from which

The original bearing tree:

A pinon, 10 ins. diam., bears S. $30\frac{3}{4}^{\circ}$ E., 105 lks. dist., re-marked T14N R41E $\frac{1}{4}$ S12 BT.

The new bearing tree:

A pinon, 10 ins. diam., bears S. 38° W., 80 lks. dist., mkd. $\frac{1}{4}$ S11 BT.

bury the original cornerstone alongside the iron post and set a steel fence post, 6 ft. long, 24 ins. in the ground alongside.

This corner is on a low spur sloping west in medium growth of sagebrush and scattering pinon.

The cor. of secs. 1, 2, 11 and 12, monumented with a granite stone, 16x12x8 ins., firmly set with a small mound of stone to W. and plainly mkd. with 5 notches on the S. face and 1 notch on the E. face.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.