

## TOWNSHIP 14 NORTH, RANGE 41 EAST

## CHAINS

The  $\frac{1}{4}$  sec. cor. of secs. 22 and 27, monumented with a quartz stone, 24x12x8 ins., firmly set with a small mound of stone to N. and plainly mkd.  $\frac{1}{4}$  on the N. face.

At the corner point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 14 ins. in the ground to bedrock and in a mound of stone to cap,  $3\frac{1}{2}$  ft. base, with brass cap mkd.

T14N R41E

$\frac{1}{4}$   $\frac{S\ 22}{S\ 27}$

1965

set the original cornerstone alongside the iron post and set a steel fence post, 6 ft. long, 18 ins. in the ground alongside. Cor. is along bladed trail bearing N. and S.

The  $\frac{1}{4}$  sec. cor. of secs. 15 and 22, monumented with a granite stone, 12x10x6 ins., firmly set along bladed trail bearing N. and S. and plainly mkd.  $\frac{1}{4}$  on the N. face.

At the corner point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 22 ins. in the ground, with brass cap mkd.

T14N R41E

$\frac{1}{4}$   $\frac{S\ 15}{S\ 22}$

1965

bury the original cornerstone alongside the iron post, set a steel pipe, 8 ft. long, 2 ins. diam., 24 ins. in the ground alongside and raise a mound of stone, 2 ft. base, 2 ft. high, N. of cor.

This corner is 1 chain east of a wash.

## TOWNSHIP 15 NORTH, RANGE 41 EAST.

These field notes are those of a remonumentation of certain corners of the survey executed by Hatch, Bridges and Barker, Deputy Surveyors, in 1873.

The cor. of secs. 13, 18, 19 and 24, monumented with a quartz stone, 14x12x8 ins., firmly set in a small mound of stone, and plainly mkd. with 3 notches on the S. face.

At the corner point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 22 ins. in the ground, with brass cap mkd.

T15N

R41E R42E

$\frac{S\ 13}{S\ 24}$   $\frac{S\ 18}{S\ 19}$

1965