

## TOWNSHIP 15 NORTH, RANGE 41 EAST

CHAINS

bury the original cornerstone alongside the iron post, set a steel fence post, 6 ft. long, 24 ins. in the ground alongside and raise a mound of stone, 2 ft. base, 2 ft. high, W. of cor. Corner is 80 lks. E. of cor. of fence bearing N. and W.

The cor. of secs. 1, 2, 35 and 36, monumented with a granite stone, 16x8x6 ins., firmly set with a small mound of stone to W. and plainly mkd. with 1 notch on the E. face and 5 notches on the W. face.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

|             |             |
|-------------|-------------|
| T15N        | R41E        |
| <u>S 35</u> | <u>S 36</u> |
| S 2         | S 1         |
| T14N        |             |

1965

bury the original cornerstone alongside the iron post, set a steel fence post, 6 ft. long, 24 ins. in the ground alongside and raise a mound of stone, 2 ft. base, 2 ft. high, W. of cor.

This corner is on a gradual W. slope. A fence bearing northerly and southerly is 5 chains west of corner.

The ¼ sec. cor. of secs. 25 and 36, monumented with a granite stone, 12x6x6 ins., firmly set in cor. of fence bearing N. and W. and plainly mkd. ¼ on the S. face.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

|               |             |
|---------------|-------------|
| T15N          | R41E        |
| ¼ <u>S 25</u> | <u>S 36</u> |

1965

bury the original cornerstone alongside the iron post.

Ravine draining NW. is 4 chains N. Small wash draining N. is 2 chains W.

The ¼ sec. cor. of secs. 13 and 24, monumented with a granite stone, 36x24x16 ins., firmly set and plainly mkd. ¼ on the S. face.

At the corner point