

TOWNSHIP 15 NORTH, RANGE 41 EAST

CHAINS

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

T15N R41E

 $\frac{S}{13}$ $\frac{1}{4} \frac{S}{24}$

1965

reset the original cornerstone alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor. Corner is 3 lks. N. of cor. of fence bearing S. and E. Cottonwood Creek is approximately 10 chains E.

TOWNSHIP 15 NORTH, RANGE 42 EAST

These field notes are those of a remonumentation of certain corners of the survey executed by Hatch, Bridges and Barker, Deputy Surveyors, in 1873.

The cor. of secs. 5, 6, 7 and 8, monumented with a quartz stone, 14x10x10 ins., firmly set and plainly mkd. with 5 notches on the S. face and 5 notches on the E. face.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

T15N R42E

 $\frac{S}{6} \frac{S}{5}$ $\frac{S}{7} \frac{S}{8}$

1965

bury the original cornerstone alongside the iron post and set a steel fence post, 6 ft. long, 24 ins. in the ground alongside.

This corner is on a gradual NW. slope in medium growth of sagebrush. Washington Creek, draining NNW. is 2 chs. E.

The $\frac{1}{4}$ sec. cor. of secs. 5 and 8, monumented with a quartz stone, 14x12x8 ins., firmly set and plainly mkd. $\frac{1}{4}$ on the N. face.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

T15N R42E

 $\frac{S}{5}$ $\frac{1}{4} \frac{S}{8}$

1965

bury the original cornerstone alongside the iron post