

TOWNSHIP 15 NORTH, RANGE 42 EAST

CHAINS

and set a steel fence post, 6 ft. long, 24 ins. in the ground alongside.

This corner is on gradual W. slope in medium growth of sagebrush and scattering juniper and pinon. Fence bearing NNE. and SSW. is 2.50 chains E.

TOWNSHIP 17 NORTH, RANGE 43 EAST

These field notes are those of a remonumentation of certain corners of the survey executed by Thurtell and Kearney, Deputy Surveyors, in 1909.

The witness cor. of secs. 33 and 34, monumented with a quartz stone, 18x6x6 ins., firmly set and plainly mkd. with 3 notches on the E. face, 3 notches on the W. face and WC on the N. face and witnessed as described in the official record.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T18N	R43E
S 33	S 34
↓	
WC	
S 3	
T17N	

1965

bury the original cornerstone alongside the iron post, set a steel fence post, 6 ft. long, 24 ins. in the ground alongside and raise a mound of stone, 2 ft. base, 2 ft. high, N. of cor.

This witness corner is on a W. slope in a reseeded area. Spur sloping NW. is 1 chain N. Porter Canyon is 5 chains N.

The closing cor. of secs. 3 and 4, monumented with a quartz stone, 18x12x8 ins., firmly set with a small mound of stone to S. and dimly mkd. with 3 notches on the E. face.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T18N	R43E
S 33	
S 4	S 3
T17N	
CC	

1965