

TOWNSHIP 17 NORTH, RANGE 43 EAST

CHAINS

bury the original cornerstone alongside the iron post, set a steel fence post, 6 ft. long, 24 ins. in the ground alongside and raise a mound of stone, 2 ft. base, 2 ft. high, S. of cor.

The $\frac{1}{4}$ sec. cor. of secs. 4 and 33, monumented with a quartz stone, 12x8x6 ins., firmly set with small mound of earth to N. and plainly mkd. $\frac{1}{4}$ on the N. face.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

T18N R43E
 $\frac{1}{4}$ $\frac{S\ 33}{S\ 4}$
 T17N

1965

bury the original cornerstone alongside the iron post, set a steel fence post, 6 ft. long, 24 ins. in the ground alongside and raise a mound of stone, 2 ft. base, 2 ft. high, N. of cor.

This corner is on gradual NW. slope in medium growth of sagebrush. Ravine from First Canyon draining NW. is 6 chains S. and 6 chains W.

The cor. of secs. 19, 24, 25 and 30, monumented with a granite stone, 20x10x6 ins., firmly set and plainly mkd. with 4 notches on the N. face and 2 notches on the S. face.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

T17N
 R42E R43E
 $\frac{S\ 24}{S\ 25}$ $\frac{S\ 19}{S\ 30}$

1965

bury the original cornerstone alongside the iron post, set a steel fence post, 6 ft. long, 24 ins. in the ground alongside and raise a mound of stone, 2 ft. base, 2 ft. high, W. of cor.

This corner is on gradual W. slope in reseeded area approximately 31 chains east of fence bearing NNE. and SSW.

The $\frac{1}{4}$ sec. cor. of secs. 19 and 24, monumented with a