

TOWNSHIP 17 NORTH, RANGE 43 EAST

CHAINS

limestone, 14x10x8 ins., firmly set and plainly mkd.
 $\frac{1}{4}$ on the W. face.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins.
 in the ground, with brass cap mkd.

T17N
 R42E R43E
 $\frac{1}{4}$
 S 24 | S 19

1965

bury the original cornerstone alongside the iron post
 and set a steel fence post, 6 ft. long, 24 ins. in the
 ground alongside.

This corner is on gradual W. slope in reseeded area
 approximately 1.50 chains east of fence bearing NNE.
 and SSW.

The cor. of secs. 13, 18, 19 and 24, monumented with a
 limestone, 16x13x6 ins., firmly set and plainly mkd.
 with 3 notches on the N. face and 3 notches on the S.
 face.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 18 ins.
 in the ground and in a collar of stone, with brass cap
 mkd.

T17N
 R42E R43E
 S 13 | S 18
 S 24 | S 19

1965

bury the original cornerstone alongside the iron post,
 set a steel fence post, 6 ft. long, 24 ins. in the
 ground alongside and raise a mound of stone, 2 ft. base,
 2 ft. high, W. of cor.

This corner is on gradual W. slope in medium growth
 of sagebrush approximately 24 chains W. of fence bearing
 NNE. and SSW.

The cor. of secs. 9, 10, 15 and 16, monumented with a
 slate stone, 18x16x4 ins., firmly set and plainly mkd.
 with 4 notches on the S. face and 3 notches on the E.
 face and witnessed by the original bearing trees.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 16 ins.
 in the ground to bedrock and in a mound of stone to cap,