Remonumentation of Corners, T. 16 N., R. 44 E.

Chains

T. 16 N., R. 44 E., M. D. Mer., Nevada

The standard corner of Ts. 16 N., Rs. 43 and 44 E., M.D. Mer., on the 3rd Stan. Par. N., which is marked by a blue limestone, 15x10x8 ins., marked with SC 16 N. and 6 grooves on N., 43 E. and 6 grooves on W., and 44 E. and 6 grooves on E. face; firmly set in the ground, and witnessed by a small mound of stone N. of cor.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, over broken glass, with the original cor. stone buried on S. edge of post; brass cap mkd.

SC T16N R43E | R44E S36 | S31

1961

Place collar of rock around post, and rebuild mound of stone N.

Corner located on a gentle E. slope on W. side of Smoky Valley, approximately 1 mile E. from base of mountains and about $\frac{1}{2}$ mile S. of Kingston Creek.

At the corner of secs. 25, 30, 31, and 36, on W. bdy. of T. 16 N., R. 44 E., which is marked with a slate rock, 26x12x9 ins., marked with 1 groove on S., and 5 grooves on N. face; firmly set in ground and surrounded by a small mound of stone. No other accessories.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 8 ins. in the ground to bedrock, over broken glass deposit and with the original cor. stone set on E. edge of post; brass cap mkd.

T16N R43E R44E <u>S25 S30</u> S36 S31 1961

Raise a mound of stone, 4 ft. base, 2 ft. high, around post.

At the ½ sec. cor. of secs. 25 and 30, on W. bdy. of T. 16 N., R. 44E. which is marked with a slate stone, 22x6x4 ins., marked ½ on W. face; firmly set in the ground, and witnessed by few scattered rock. No evidence found of the 2 original bearing trees.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, over broken glass, with original cor. stone buried on W. side of post; brass cap mkd.

T16N
R43E R44E

\$\frac{1}{2}\$
S25|S30
|
1961

From which

A juniper, 6 ins. diam., bears N. 50° E., 30 1ks. dist.,