

Remonumentation of Corners, T. 17 N., R. 44 E., M.D. Mer.

Chains

T. 17 N., R. 44 E., M.D. Mer.

At the corner of secs. 32 and 33, on the S. bdy. of T. 17 N., R. 44E. which is marked with a slate stone, 15x13x10 ins., marked with 4 grooves on E. and 2 grooves on W. face; firmly set in the ground, and witnessed by a small mound of stone on the W.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, over broken glass deposit, and original cor. stone buried against S. side of post; brass cap mkd.

T17N	R44E
S32	S33

1961

Place collar of rock around, and rebuild mound of stone W. of cor.

Corner is located on a gradual SE. slope, about ¼ mile W. of stream in ditch, draining SE., and approximately ½ mile E. of base of mountains.

At the ¼ sec. cor. of secs. 4 and 33, on S. bdy. of T. 17 S., R. 44E. marked by a quartzite stone, 25x8x6 ins., marked with ¼ on N. face; set in small mound of stone, and witnessed by a small mound of stone on the W.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, over broken glass, and with original cor. stone buried on E. edge of post; brass cap mkd.

T17N	R44E
¼	S33
	S 4
	T16N

Place collar of rock around, and rebuild the mound of stone, N. of cor.

Corner located on gradual SE. slope in Smoky Valley, approximately 15 chs. E. of stream in ditch, drains SE.

At the ¼ sec. cor. of secs. 28 and 33, T. 17 S., R. 44 E., which is marked with a blue limestone, 17x10x5 ins., marked ¼ on N. face; set in small mound of stone, and witnessed by a small mound of stone N.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, over broken glass, and with original cor. stone buried on N. edge of post; brass cap mkd.

T17N	R44E
¼	S28
	S33
	1961

Raise a mound of stone around, and rebuild mound on the N.

Corner is located near head of very small drain, course SE. in widely scattered scrub junipers.