

Remonumentation of Corners, T. 17 N., R. 44 E., M.D. Mer.

Chains

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with original cor. stone buried on W. side; brass cap mkd.

T17N R44E

¼ S3

1961

Place collar of rock around, and rebuild mound of stone W.

Note: From this ¼ sec. cor., S. 3.13 chs. dist (measured) I found a ¼ sec. cor. for W. bdy., sec. 2, marked by a quartz stone, showing 17x12x6 ins., correctly set, mkd. and witnessed. No record was found of its establishment in the survey notes. Not remonumented.

At the cor. of secs. 2 and 3, on the N. bdy. of T. 17 N., R. 44 E., which is a granite stone, 18x10x7 ins., marked with 2 notches on E., and 4 notches on W. edge; witnessed by a small mound of stone on the S., and 2 original bearing trees.

from which

A pinon, 10 inches diam., bears S. 41½° E., 126 lks. dist., mkd. T 17 N., R 44 E., S2 BT.

A pinon, 8 inches diam., bears S. 4½° W., 93 lks. dist., blazed and having dim scribe marks.

At cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, over broken glass; orig. cor. stone buried on S. side of post; brass cap mkd.

T18N R44E

S34

S 3 | S 2

T17N | R44E

1961

Place collar of rock around post.

At the ¼ sec. cor. on N. bdy. sec. 2, T. 17 N., R. 44 E., which is a granite stone, 18x9x4 ins., marked ¼ on N. face, firmly set, and witnessed by a small mound of stone, N. of cor.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, over broken glass, and orig. cor. stone buried on S. side of post; brass cap mkd.

¼ S 2

T17N R44E

1961

Place collar of rock around, and rebuild mound of stone, S. of cor.

The ¼ sec. cor. on S. bdy., sec. 35, T. 18 N., R. 44 E., bears E. 1.94 chs. dist. (new measurement) (record dist. 1.72 chs.).