

Remonumentation of Corners, T. 18 N., R. 45 E., M.D. Mer.

Chains

post; brass cap mkd.

T18N R45E
S 4
1/4 S 9
1961

Dig pits, E. and W., and enlarge earth mound N. of cor. No rock available. No suitable trees within limits in sec. 9.

At the cor. of secs. 3, 4, 9 and 10, T. 18 N., R. 45 E., which is a granite stone, 17x10x7 ins., marked with 3 notches on E. and 5 notches on S. edge; firmly set, and witnessed by a mound of stone, 2x2 ft. W. of cor.

At the cor. point

Set an iron post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over broken glass, with original cor. stone buried on W. side of post; brass cap mkd.

T18N R45E
S 4 S 3
S 9 S 10
1961

Place collar of rock around post.

At the 1/4 sec. cor. of secs. 3 and 4, T. 18 N., R. 45 E., which is a granite stone, 13x13x8 ins., marked 1/4 on the W. face, firmly set in ground, witnessed by evidence of pit on the S. and earth mound on the W., and also 1 bearing tree

from which

A juniper, 16 ins. diam., bears N. 23° E., 155 lks. dist., mkd. T18N R45E S3 BT.

At the cor. point

Set an iron post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over broken glass, with original cor. stone buried on W. side of post; brass cap mkd.

1/4
T18N R45E
S4 S3
1961

Raise a mound of stone to top, around post.

Corner is located on gentle NE. slope, about 80 lks. dist. S. of wash in ravine, drains SE.

At the cor. of secs. 3 and 4, on N. bdy. T. 18 N., R. 45 E., which is a dark granite stone, 18x14x9 ins., marked with 3 grooves and 45E on E., and 3 grooves and 18 N. on W. face; firmly set, and witnessed by 2 bearing trees and evidence of earth mound on the S.

from which

A juniper, 6 ins. diam., bears S. 86° E., 150 lks. dist., scribe marks too weathered to be legible.