Remonumentation of Corners, T. 18 N., R. 45 E., M.D. Mer.

## Chains

A juniper, 8 ins. diam., bears S. 9° W., 20 1ks. dist., mkd. T18N R45E S4 BT.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 14 ins. in the ground, to rock, over broken glass, with original cor. stone, buried alongside of post; brass cap mkd.

Raise a mound of stone to top, around post.

Corner is located on gentle NE. slope, about 1 ch. N. top of hill, and W. about 75 lks. dist. from a 4 strand wire fence, bears N. 35° E. and S. 35° W.

At the  $\frac{1}{2}$  sec. cor. of sec. 3, on N. bdy. T. 18 N., R. 45 E., which is a granite stone, 14x13x5 ins., marked  $\frac{1}{2}$  on N. face, firmly set, and witnessed by distinct evidence of earth mound on the N.

At the cor. point

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, over broken glass, and with original cor. stone buried on S. side of post; brass cap mkd.

Place collar of rock around, and raise a mound of stone, 2x12 ft. S. of cor. A small wash draining NE. is 40 lks. E. of cor.

The ½ sec. cor. on S. bdy. sec. 34, T. 19 S., bears E. 4.49 chs. dist. (record 4.40 chs.)

Remonumentation of Corner, T. 19 N., R. 43 E., M.D. Mer.

The west, south and north boundaries and a portion of the east boundary and a portion of the subdivisional lines of T. 19 N., R. 43E. M.D. Mer. were surveyed by Tracy in 1867 and 1868.

The following field notes are those of the remonumentation of certain identified original corners in T. 19 N., R. 43 E., Mt. Diablo Mer., Nevada. The position of each corner was mkd. by the original monument or determined from corner accessories recorded in the original survey record.

The corners remonumented were selected by the Forest Service as being adjacent to, or controlling the boundaries of Forest Service Lands. The remonumentation was requested by and accomplished in cooperation with the Forest Service.

T. 19 N., R. 43 E., M.D. Mer.

At the cor. of secs. 24 and 25, on E. bdy., T. 19 N., R. 43 E.,