

Remonumentation of Corners, T. 12 N., R. 44 E.

Chains

At the $\frac{1}{4}$ sec. cor. of secs. 25 and 36, monumented by a granite stone, 24x9x4 ins., firmly set, mkd. with $\frac{1}{4}$ on N. face; witnessed by a mound of stone, 2x1 $\frac{1}{2}$ ft., N. of cor.

At cor. point

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, over broken glass; original corner stone buried on N. side of post; brass cap marked

T12N R44E

$\frac{1}{4}$ $\frac{S25}{S36}$

1961

Place collar of rock around post.

At the $\frac{1}{4}$ sec. cor. of secs. 31 and 36, on E. bdy. of T. 12 N., R. 44 E., monumented by a granite stone, 19x8x7 ins., firmly set, mkd. $\frac{1}{4}$ on W. face; witnessed by a small mound of stone W. of cor.

At cor. point

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 15 ins. in the ground to rock, over broken glass, and supported in a mound of stone to top; brass cap marked

T12N

R44E R45E

$\frac{1}{4}$
S36|S31

1961

At the cor. of secs. 25, 30, 31 and 36, on E. bdy. T. 12 N., R. 44 E., monumented by a granite stone, 14x6x5 ins., firmly set, mkd. 1 groove on S. and 5 grooves on N. face; witnessed by a small mound of earth and stone, W. of cor.

At cor. point

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 10 ins. in the ground to rock, over broken glass; original corner stone set alongside of post; brass cap marked

T12N

R44E R45E

$\frac{S25}{S36}$ | $\frac{S30}{S31}$

1961

Raise a mound of stone, 4 ft. base to top, around cor.

At the witness $\frac{1}{4}$ sec. cor. of secs. 25 and 30, on E. bdy. of township, (N. 69 lks. dist. from true point, by record) monumented by a white rhyolite stone, 14x10x5 ins., mkd. $\frac{1}{4}$ on W. face, and set in a small mound of stone, on top of barren rock slope; witnessed.

At cor. point